



5 THREAD EXTRA HEAVY DUTY  
TOP FEED MACHINE



OV 636-555

## Global OV 630 Series OVERLOCK MACHINES WITH TOP AND DIFFERENTIAL FEED

### OV 630

High speed two needle and safety stitch overlock machines with top feed combined with differential feed.

Máquina overlock, 5-hilos con puntada de seguridad, de alta velocidad. Equipada con arrastre superior combinado con transporte diferencial inferior.

Hochleistungs-Zweinadel Safetymaschinen mit vor den Nadeln liegendem Obertransport kombiniert mit einem Differentialtransport.

Surjeteuse à grande vitesse à deux aiguilles et point safety, griffe supérieur devant les aiguilles combinée avec entraînement différentiel.

### SPECIFICATIONS OV 630 SERIES

TYPE MODEL	STITCH TYPE	NUMBER OF NEEDLES	NUMBER OF THREADS	NEEDLE DISTANCE MM	OVEREDGING (MM) WIDTH WIDTH OVERALL	STITCH LENGTH MM	DIFFERENTIAL FEED RATIO	PRESSER FOOT LIFT (MM)	MAX. SEWING SPEED
OV 634-240		2	4	2	4 6	4	1:0.7 - 1:2 1:0.8 - 1:2	6	5500
OV 636-550		2	5	5	5 10	4	1:0.7 - 1:2 1:0.8 - 1:3.5	6	5000
OV 636-555		2	5	5	5 10	4	1:0.7 - 1:2 1:0.8 - 1:2	6.5	5000
OV 636-558		2	5	5	5 10	5	1:0.7 - 1:2 1:0.8 - 1:2	8	5000

### TECHNICAL SPECIFICATIONS

**MACHINE SPEED**  
max 5500 spm

**STITCH LENGTH**  
2,5 - 5 mm

**FEED TYPE**  
differential feed

**BOTTOM DIFFERENTIAL FEED RATIO**  
1:0.7 - 1:2

**LONGITUDE STROKE OF TOP FEED DOG**  
2.7 - 7 mm

**PRESSER FOOT LIFT**  
max 8 mm

**NEEDLE TYPE**  
B-27

**NEEDLE TYPE OV-636-558**  
B-64